

506 Conical Monopole Antenna

The Model 506 family of conical monopole antennas utilizes a new class of radiating structure which, when combined with structural innovations, results in an extremely simple installation and a broader operating bandwidth than previous versions of this type of antenna. The novel TCI radiating configuration maintains the pattern close to the ground over a six-to-one bandwidth. The pattern of conventional conical monopoles rises after a four-to-one bandwidth has been covered.

Simplify installation while enhancing bandwidth and pattern control.

In the 506, guys perform their usual structural function and serve as part of the radiating structure as well. No "spreader tubes" or difficult rigging tolerances are involved. The 506 series is entirely aluminum. No dissimilar metals are employed anywhere in the antenna.



All TCI antennas share the same high-quality, exhaustively tested components and materials. All radiators, feedlines, and catenaries are Alumoweld, a wire composed of a high-strength steel core and a highly conductive, corrosion-resistant, welded coating of aluminum. All feedline and radiator tip insulators are made of high-strength glazed alumina, a material with an extremely low loss tangent (0.001), which is virtually impervious to the effects of ultraviolet radiation, dirt, and salt spray.

KEY FEATURES

- › Up to 7:1 impedance and pattern bandwidth
- › Lowest total installed cost
- › 2.5:1 VSWR max

506 System Details

Model 506 Elevation Patterns and Impedance Data



Model 506 Specifications

Polarization	Vertical
Azimuth Plane Pattern	circular within ± 0.5 dB
Nominal TOA	suitable for shore-ship; see patterns
VSWR	2.5:1 Max
Power Handling Capability	up to 100 kW Peak with special end seal
Bandwidth	up to 7:1
Environmental Performance	Designed in accordance with EIA Specification RS-222C to withstand forces of 225 km/h (140 mi/h) wind, no ice 145 km/h (90 mi/h) wind, 12 mm (1/2") radial ice.

› Size

Model Number	Frequency Range	Height		Length or Width	
		ft.	m	ft.	m
506-1-N	2–14 MHz	82	25.0	162	49.4
506-2A-N	3–21 MHz	52	15.8	108	32.9
506-6-N	5–30 MHz	32	9.8	66	20.1
506-7-N	4–24 MHz	42	12.8	80	24.4

* Measured from extreme guy points

› Power and Impedance Data

Model Number	Input Impedance	Power	Connector
506-N-02	50 Ω coaxial	Receive	Type N Female
506-N-03	50 Ω coaxial	1 kW avg/2 kW PEP	Type N Female
506-N-28	50 Ω coaxial	5 kW avg/10 kW PEP	7/8" EIA Female
506-N-03	50 Ω coaxial	10 kW avg/50 kW PEP	1-5/8" EIA Female
506-N-04	50 Ω coaxial	20 kW avg/70 kW PEP	3-1/8" EIA Female



TCI INTERNATIONAL, INC.

3541 Gateway Blvd.

Fremont, CA 94538-6585 USA

TEL: 1-510-687-6100

USA: 1-800-824-8074

FAX: 1-510-687-6101

www.tcibr.com

Specialized Expertise in a Global Family

TCI International, Inc., a leading supplier of end-to-end, ITU-compliant RF spectrum monitoring and management solutions, is a wholly-owned subsidiary of SPX Corporation. Headquartered in Charlotte, North Carolina, SPX is a multi-industry, Fortune 500 enterprise with operations in more than 35 countries and approximately 18,000 associates worldwide. SPX team members collaborate across business segments and borders to deliver greater efficiencies and better ideas for helping customers succeed and grow their businesses.

At TCI, this commitment to innovation serves civilian spectrum regulatory departments and provides COMINT, ISR, and DF solutions for Military, National Security and Intelligence agencies.

TCI has developed high-performance RF and spectrum monitoring solutions for more than 40 years. Our complete, in-house hardware and software engineering capabilities include RF/analog equipment design, system engineering and integration, digital Signal Processing (DSP) design and implementation and expert client-server software design and development.

SPX[®]



Company proprietary

Data and specifications subject to change without notification

Not for distribution without prior permission from TCI.

506-10-10-12

©2004-2012 TCI—All Rights Reserved